

AS-5 Packer

The AS-5 Packer is a compression set tool with a J-slot to control pack-off. It is run above other packers such as the ASIII to selectively treat, produce or inject in multiple zone completions. It is also used to isolate casing hole perforations. The AS-5 features a large bypass area to prevent swabbing when running and retrieving. Releasing the valve allows debris to be washed from the upper slips.

Special Features

- Large internal bypass
- Mechanical slips vs. hydraulic buttons
- Additional J-slot arrangements available

Specification Guide

Casing				Packer			Part Number
O.D.	Weight lb/ft	Min I.D.	Max I.D.	O.D.	I.D.	Thread Connection Box up/Pin down	
4½	9.5 - 13.5	3.920	4.090	3.750	1.937	2¾ EUE	60845
5½	14.0 - 20.0	4.778	5.012	4.625	2.375	2¾ EUE	60856
5½	20.0 - 23.0	4.670	4.778	4.500	2.000	2¾ EUE	60857
7	26.0 - 32.0	6.094	6.276	5.875	2.500	2¾ EUE	60870
7	17.0 - 26.0	6.276	6.538	6.000	2.500	2¾ EUE	60872
7	17.0 - 26.0	6.276	6.538	6.000	3.000	3½ EUE	60874

* Other sizes and connections available on request

