



ASIII Packer

The ASIII Packer is a single grip packer with no upper hold down for use where no differential pressure from below is present. From the packing elements down, the ASIII operates identically to the ASII. The ASII also features a large bypass area to prevent swabbing when running or retrieving. The ASIII is ideal for isolating casing holes or perforations when used as the lower packer in conjunction with the Snapset as the upper packer.

Special Features

- Large internal bypass
- Optional setting bottoms
- ¼ turn set/straight pick up release
- Additional J-slot arrangements available

Specification Guide

Casing				Packer			Part Number
O.D.	Weight lb/ft	Min I.D.	Max I.D.	Max O.D.	Max I.D.	Thread Connection Box up/Pin down	
3½	7.7 - 10.2	2.922	3.068	2.781	1.25	1.900 NU	63135
4½	9.5 - 13.5	3.920	4.090	3.750	1.87	2¾ EUE	63145
5½	14.0 - 20.0	4.778	5.012	4.625	1.94	2¾ EUE	63155
5½	15.5 - 17.0	4.892	4.950	4.625	2.38	2¾ EUE	63156
5½	20.0 - 23.0	4.670	4.778	4.500	2.00	2¾ EUE	63157
5½	14.0 - 20.0	4.778	5.012	4.625	2.38	2¾ EUE	63158
6¾	17.0 - 24.0	5.920	6.135	5.750	2.50	2¾ EUE	63165
7	26.0 - 32.0	6.094	6.276	5.875	2.50	2¾ EUE	63170
7	17.0 - 26.0	6.276	6.538	6.000	2.50	2¾ EUE	63172
7	26.0 - 32.0	6.094	6.276	5.875	3.00	3½ EUE	63173
7¾	24.0 - 29.7	6.875	7.025	6.672	2.50	2¾ EUE	63175
9¾	43.5 - 53.5	8.535	8.755	8.250	2.50	2¾ EUE	63198

* Other sizes and connections available on request