



GV-Cup Packer

The GV Cup Packer is an economical means for isolating casing leaks and depleted zones and is also a production or injection packer for low pressure applications. This packer can be run with cups opposing or in the same direction depending on the application. The GV Cup Available with packing element backup rings for higher pressure applications and comes in a full range of tubing and casing sizes in two or four cup models.

Specification Guide

| Casing Size | Packer I.D. | Thread Connection | Part Number |
|-------------|-------------|-------------------|-------------|
| 3½ | 1.50 | 1.900 NU | 43935 |
| 4½ | 2.00 | 2¾ EUE | 43945 |
| 4½ | 2.50 | 2¾ EUE | 43946 |
| 5½ | 3.00 | 3½ EUE | 43953 |
| 5½ | 2.00 | 2¾ EUE | 43955 |
| 5½ | 2.50 | 2¾ EUE | 43956 |
| 6¾ | 3.00 | 3½ EUE | 43965 |
| 6¾ | 4.00 | 4½ LTC | 43966 |
| 7 | 2.50 | 2¾ EUE | 43970 |
| 7 | 4.00 | 4½ LTC | 43971 |
| 7 | 3.00 | 3½ EUE | 43973 |
| 7 | 4.00 | 4½ LTC | 43974 |
| 8¾ | 2.50 | 2¾ EUE | 43985 |
| 9¾ | 3.00 | 3½ EUE | 43976 |
| 9¾ | 4.00 | 4½ LTC | 4391075 |

** Other sizes and connections available on request*