



Snapset I Packer

The Snapset I Packer is a compression set tool requiring only straight set down weight to pack-off. It is run above other packers such as the ASIX, ASII or ASIII for selective production to isolate casing holes and perforations. This packer has no upper or lower slips and should be used only where intermediate differential pressures from below are expected. The Snapset has an internal latch to prevent the packer from presetting when running down the hole. When releasing, the latch re-engages to allow movement down hole.

Special Features

- Large internal bypass
- Set down to pack off, pick up to release
- Compact design

Specification Guide

Casing				Packer			Part Number
O.D.	Weight lb/ft	Min I.D.	Max I.D.	O.D.	I.D.	Thread Connection Box up/Pin down	
3½	7.7 - 10.2	2.922	3.068	2.781	1.25	1.900 NU	63535
4½	9.5 - 13.5	3.920	4.090	3.750	1.94	2¾ EUE	63545
5½	14.0 - 20.0	4.778	5.012	4.625	2.00	2¾ EUE	63555
5½	14.0 - 20.0	4.778	5.012	4.625	2.38	2¾ EUE	63556
5½	20.0 - 23.0	4.670	4.778	4.500	2.00	2¾ EUE	63557
5½	20.0 - 23.0	4.670	4.778	4.500	2.37	2¾ EUE	63558
7	26.0 - 32.0	6.094	6.276	5.875	2.50	2¾ EUE	63570
7	17.0 - 26.0	6.276	6.538	6.000	2.50	2¾ EUE	63572
7¾	24.0 - 29.7	6.875	7.025	6.672	2.50	2¾ EUE	63575

* Other sizes and connections available on request