



T-2 On-Off Tool

The Type T-2 On-Off Tool is a tubing seal receptacle allowing isolation of a lower zone using a wireline blanking plug. The tubing string can then be removed from the well. When re-run, the tubing string automatically re-engages to the stinger, and the blanking plug can be retrieved by wireline.

The T-2 runs above an ASI-X, VSI-XW or Permanent Packer with latch stinger.

Special Features

- Blanking plug seats in top of stinger to prevent debris build-up
- Bonded seal allows disconnects and reconnects
- Right or left hand release
- Milling shoe allows rotation through debris

Specification Guide

Casing/Tubing Size	Tool O.D.	Thread Connection Box up/Pin down
2 $\frac{7}{8}$	2.250	1.900 NU
3 $\frac{1}{2}$	2.750	1.900 EUE
4	3.250	1.900 EUE
4	3.250	2 $\frac{3}{8}$ EUE
4 $\frac{1}{2}$	3.750	2 $\frac{3}{8}$ EUE
5 $\frac{1}{2}$	4.500	2 $\frac{3}{8}$ EUE
5 $\frac{1}{2}$	4.500	2 $\frac{7}{8}$ EUE
6 $\frac{5}{8}$	5.500	2 $\frac{3}{8}$ EUE
6 $\frac{5}{8}$	5.500	2 $\frac{7}{8}$ EUE
7	5.875	2 $\frac{3}{8}$ EUE
7	5.875	2 $\frac{7}{8}$ EUE
7	5.875	3 $\frac{1}{2}$ EUE
7 $\frac{5}{8}$	6.375	2 $\frac{3}{8}$ EUE
7 $\frac{5}{8}$	6.375	2 $\frac{7}{8}$ EUE
7 $\frac{5}{8}$	6.375	3 $\frac{1}{2}$ EUE
7 $\frac{5}{8}$	6.375	4 $\frac{1}{2}$ EUE
8 $\frac{5}{8}$	7.500	2 $\frac{3}{8}$ EUE
8 $\frac{5}{8}$	7.500	2 $\frac{7}{8}$ EUE
8 $\frac{5}{8}$	7.500	3 $\frac{1}{2}$ EUE
8 $\frac{5}{8}$	7.500	4 $\frac{1}{2}$ EUE
9 $\frac{5}{8}$	8.250	2 $\frac{3}{8}$ EUE
9 $\frac{5}{8}$	8.250	2 $\frac{7}{8}$ EUE
9 $\frac{5}{8}$	8.250	3 $\frac{1}{2}$ EUE
9 $\frac{5}{8}$	8.250	4 $\frac{1}{2}$ EUE
10 $\frac{3}{4}$	9.000	2 $\frac{3}{8}$ EUE
10 $\frac{3}{4}$	9.000	2 $\frac{7}{8}$ EUE
10 $\frac{3}{4}$	9.000	3 $\frac{1}{2}$ EUE
10 $\frac{3}{4}$	9.000	4 $\frac{1}{2}$ EUE
11 $\frac{3}{4}$	10.000	2 $\frac{3}{8}$ EUE
11 $\frac{3}{4}$	10.000	2 $\frac{7}{8}$ EUE
11 $\frac{3}{4}$	10.000	3 $\frac{1}{2}$ EUE
11 $\frac{3}{4}$	10.000	4 $\frac{1}{2}$ EUE

* Other sizes and connections available on request