

Type DL-1 Tandem Tension Packer

The DL-1 Tandem Tension Packer is an economical, compact, low-pressure, tension set, isolation packer used in casing or perforations and multi-zone injection installations. This packer runs with a tension set packer below. It can be run with the j-pins in the unjayed or jayed position. In the unjayed position applying tension shears the shear pins and allows pack-off. If run in the jayed position the DL-1 must be used with the ASI-X Packer. Set down weight shears the pins and left-hand rotation and applied tension will set the tool.

Special Features

- Economical
- Run in jayed or unjayed position
- Optional J's available

Specification Guide

Casing				Packer			Part Number
O.D.	Weight lb/ft	Min I.D.	Max I.D.	O.D.	I.D.	Thread Connection Box up/Pin down	
3½	7.7 - 10.3	2.922	3.068	2.781	1.53	1.900 EUE	43735
4½	9.5 - 13.5	3.920	4.090	3.750	1.94	2¾ EUE	43745
4½	9.5 - 11.6	4.000	4.090	3.844	2.38	2¾ EUE	43746
5	15.0 - 18.0	4.276	4.408	4.125	2.00	2¾ EUE	43750
5½	13.0 - 20.0	4.778	5.044	4.625	2.00	2¾ EUE	43756
7	17.0 - 29.0	6.184	6.538	6.000	2.50	2¾ EUE	43770
7	17.0 - 29.0	6.184	6.538	6.000	3.00	3½ EUE	43773
7¾	29.7 - 33.7	6.765	6.875	6.500	2.50	2¾ EUE	43775
9¾	40.0 - 47.0	8.681	8.835	8.250	2.50	2¾ EUE	43795
9¾	40.0 - 43.5	8.755	8.835	8.500	3.00	3½ EUE	43796

* Other sizes and connections available on request